

SPECIFICATION

MODE NO.	CT-63KR11HN		CT-63KR11HP
TV SYSTEM	NTSC		PAL
IMAGE SENSOR	1/3-inch CCD Image Sensor		
CCD TOTAL PIXELS	816(H) x 495(V)		798(H) x 584(V)
SCANNING SYSTEM	525 lines, 60 fields/sec		625 lines, 50 fields/sec
SYNC SYSTEM	Internal		
MINIMUM ILLUMINATION	0.8 Lux F1.2		5600°K
LENS & VIEW ANGLE	-		
RESOLUTION	470 TVL / 580 TVL (Enhanced)		
WHITE BALANCE	Mode	ATW / AWB Switchable	
	Range	3200 ~ 10000 °K	
GAIN CONTROL	AGC ON / OFF switchable		
S/N RATIO	52dB (MIN) / 60dB (TYP) (AGC OFF)		
ELECTRONIC SHUTTER	1/60~1/120,000 sec.		1/50~1/120,000 sec.
AUTO IRIS	VIDEO / DC / A.E.S.		
B.L.C. FUNCTION	ON / OFF switchable		
MIRROR FUNCTION	ON / OFF switchable		
DIGITAL ZOOM	ON / OFF switchable		
AUDIO OUTPUT	Low impedance output		
VIDEO OUTPUT	Composite 1.0V p-p at 75 ohm		
GAMMA CORRECTION	0.45		
OPERATION TEMPERATURE	-20°C TO 50°C		
OPERATIONAL HUMIDITY	within 85%RH		
POWER SUPPLY	DC12V±1V / 150mA		

* The specifications and appearance of the product may be changed without notice.

Dimension (Unit : mm)

